

DECLARATION OF PERFORMANCE

DOP-8314X-04

1. Unique identification code of the product-type:
8314X
2. Intended use/es:
Application: Plastic and rubber vapour control layers EN 13984
3. Manufacturer:
DuPont de Nemours (Luxembourg) S.à r.l.
Rue General Patton, L-2984 Luxembourg
4. Authorised representative:
-
5. System/s of AVCP:
System 3
- 6a. Harmonised standard:
EN 13984:2013
Notified body/ies:
NB 1396, NB 1301
7. Declared performance/s:
Harmonised technical specification EN 13984:2013

Essential characteristics			Performance		
PROPERTY	METHOD	UNITS	NOMINAL	MINIMUM	MAXIMUM
Water vapour transmission (sd)	EN 1931	m	2400	1500	-
Density of water vapour flow rate (g)	EN 1931	kg / (m ² s)	1,73E-10	-	2,77E-10
Durability (exposure to artificial ageing)					
Water vapour transmission properties	EN 1931	pass / no pass	pass	-	-
Water tightness	EN 1928 (A)	pass / no pass	pass	-	-
Reaction to fire	EN ISO 11925-2	class	E	-	-
Maximum tensile force (MD)	EN 12311-2	N/50mm	180	140	-
Elongation at max. tensile force (MD)	EN 12311-2	%	15	5	-
Maximum tensile force (XD)	EN 12311-2	N/50mm	160	120	-
Elongation at max. tensile force (XD)	EN 12311-2	%	25	10	-
Resistance to tearing MD (nail shank)	EN 12310-1	N	250	180	-
Resistance to tearing XD (nail shank)	EN 12310-1	N	280	210	-
Resistance to impact	EN 12691	mm	(+)		
Joint strength	EN 12317-2	N/5cm	(+)		
Durability (against alkali)					
Elongation at max. tensile force (MD)	EN 12311-2	pass / no pass	(+)		
Elongation at max. tensile force (XD)	EN 12311-2	pass / no pass	(+)		

(+): No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Claude Metzdorf

Managing and Works Director - DuPont Luxembourg

Luxembourg, 28/07/2016